

# Rotor 23B

- [Français](#)
- [English](#)

Downloadable files

x

## Open access

### [Git project](#)

## Original model

Rotor 23B is part of a research program to study the effects of aspect ratio, diffusion factor, and solidity on rotors. To do so, experimental studies have been conducted on a series of high-hub-tip-radius-ratio compressor stages representative of the middle and latter stages of axial-flow compressors. In fact, 14 middle stages were tested to assess the effects on performance of varying both diffusion through the rotor and stator blades and blade aspect ratio. Among these 14 stages, there are rotors 23B, 24A, 25A, 26B, 27A and 28B. Both the tip diameter and the hub-tip radius ratio were held constant throughout each stage at 50.8 centimeters and 0.8, respectively.

- Original technical report [\[1\]](#):

```
@TechReport{britsch1979design,
author      = {Britsch, Werner R. and Osborn, Walter M. and Laessig, Mark R.},
title       = {Effects of Diffusion Factor, Aspect Ratio, and Solidity on Overall Performance of 14 Compressor Middle Stages},
institution = {NASA Lewis Research Center Cleveland, OH, United States},
note        = {NASA-TP-1523, url~:
\url{https://ntrs.nasa.gov/citations/19790025039}, 1979 }}
```

- Picture :



<https://catalog.archives.gov/id/17446275>

```
@Misc{brown1975records,
author = {BROWN, M.},
title = {Rotor 23B - Stator 20B. Records of the National Aeronautics and Space Administration, 1903 - 2006. Photographs relating to agency activities, facilities and personnel, 1973 - 2013},
note = {\url{https://catalog.archives.gov/id/17446275}{https://catalog.archives.gov/id/17446275}, 1975 }, % for Fig. 1}
```

## Useful documents

- PDF of the NASA report :  
rotor23b.pdf
- CSV file of the blade geometry :  
rotor23b\_original.csv

## Geometry

The geometry of rotor 23B is described in the original NASA report by the following tables. The length are in centimeters and the angles in degrees.

TABLE 8. - BLADE GEOMETRY FOR ROTOR 23B

RP	PERCENT RADII			BLADE ANGLES			DELTA INC	CONE ANGLE
	SPAN	R1	R0	K1C	KTC	K0S		
TIP	0.	25.400	25.400	63.54	56.04	53.62	2.26	0.057
1	5.	25.168	25.146	63.31	57.75	53.11	2.44	-0.478
2	10.	24.912	24.892	63.06	57.39	52.53	2.63	-0.425
3	15.	24.656	24.638	62.00	56.98	51.83	2.83	-0.370
4	30.	23.886	23.876	62.01	55.69	49.57	3.59	-0.198
5	50.	22.856	22.860	60.91	53.92	46.51	4.11	0.079
6	70.	21.829	21.844	59.75	52.02	42.55	4.00	0.277
7	95.	21.055	21.082	58.84	51.45	39.17	5.28	0.468
8	90.	20.797	20.828	58.53	49.86	37.85	5.44	0.532
9	95.	20.538	20.574	58.22	49.16	36.15	5.59	0.600
HUB	100.	20.320	20.320	57.95	48.52	34.54	5.72	0.057

RP	BLADE THICKNESSES			AXIAL DIMENSIONS			
	T1	TM	T0	Z1C	ZMC	ZTC	Z0C
TIP	0.051	0.151	0.051	0.336	1.557	1.695	2.535
1	0.051	0.158	0.051	0.325	1.558	1.679	2.962
2	0.051	0.167	0.051	0.313	1.559	1.662	3.011
3	0.051	0.176	0.051	0.299	1.559	1.643	3.022
4	0.051	0.201	0.051	0.255	1.559	1.584	3.090
5	0.051	0.233	0.051	0.194	1.560	1.497	3.186
6	0.051	0.264	0.051	0.126	1.560	1.400	3.290
7	0.051	0.286	0.051	0.069	1.560	1.319	3.377
8	0.051	0.293	0.051	0.048	1.559	1.289	3.411
9	0.051	0.300	0.051	0.023	1.558	1.255	3.450
HUB	0.051	0.306	0.051	-0.000	1.557	1.226	3.492

## Aerodynamic design

	unit	values
<b>pressure ratio</b>	[ - ]	1.257
<b>mass flow</b>	[kg/s]	9.46
<b>tip speed</b>	[m/s]	243.8
<b>tip solidity</b>	[ - ]	1.6
<b>aspect ratio</b>	[ - ]	1
<b>number of blades</b>	[ - ]	50
<b>rotative speed</b>	[rad/s]	960.28

## Material properties

The original material of the rotor 23B is not defined in the NASA report.

Considered properties: 200-grade maraging steel :


	unité	valeurs
<b>alloy</b>	[ - ]	18-Ni-200-maraging
<b>Young's modulus</b>	[GPa]	180
<b>density</b>	[kg/m3]	8000
<b>Poisson's ratio</b>	[ - ]	0.3
<b>yield stress</b>	[GPa]	1.38

First three natural frequencies (with clamped root) for the mesh:

1. (1B): 7194.7 rad/s / 1145.1 Hz

2. (1T): 15383.6 rad/s / 2448.4 Hz
3. (2B): 28053.6 rad/s / 4464.9 Hz

## CAD



Fichiers téléchargeables

x

### Libre accès

[lien vers le projet Git](#)

## Modèle original

Le rotor 23B fait partie d'un programme de recherche visant à étudier les effets de l'allongement, du facteur de diffusion et de la solidité des rotors. Pour ce faire, des études expérimentales ont été menées sur une série d'étages de compresseurs à fort rapport entre les rayons du moyeu et de la tête d'aube, représentatifs des étages moyens et avancés des compresseurs à flux axial. En effet, 14 étages intermédiaires ont été testés pour évaluer les effets sur les performances de la variation de la diffusion et de l'allongement des aubes. Parmi ces 14 étages, on trouve les rotors 23B, 24A, 25A, 26B, 27A et 28B. Le diamètre de l'extrémité des aubes et le rapport entre les rayons du moyeu et de la tête d'aube ont été maintenus constants tout au long de chaque étage à 50.8 centimètres et 0.8, respectivement.

- Rapport technique original <sup>[1]</sup>:

```
@TechReport{britsch1979design,  
author      = {Britsch, Werner R. and Osborn, Walter M. and Laessig, Mark  
R.},  
title       = {Effects of Diffusion Factor, Aspect Ratio, and Solidity on  
Overall Performance of 14 Compressor Middle Stages},
```

```

institution = {NASA Lewis Research Center Cleveland, OH, United States},
note      = {NASA-TP-1523, url~:
\url{https://ntrs.nasa.gov/citations/19790025039}, 1979 }

```

- Photographie :



<https://catalog.archives.gov/id/17446275>

```

@Misc{brown1975records,
author    = {BROWN, M.},
title     = {Rotor 23B - Stator 20B. {R}ecords of the {N}ational {A}eronautics
and {S}pace {A}dministration, 1903 - 2006. {P}hotographs relating to agency
activities, facilities and personnel, 1973 - 2013},
note      =
{\href{https://catalog.archives.gov/id/17446275}{https://catalog.archives.gov/
id/17446275}, 1975 }, % for Fig. 1}

```

## Documents utiles

- PDF du rapport de la NASA :

rotor23b.pdf

- Fichier CSV de la géométrie :

rotor23b\_original.csv

## Géométrie

La géométrie du rotor 23B est décrite dans le [rapport d'origine de la NASA](#) par les tableaux suivants. Les grandeurs sont en centimètres et en degrés.

TABLE 8. - BLADE GEOMETRY FOR ROTOR 23B

RP	PERCENT SPAN	RADI R1	RADI R0	BLADE ANGLES	DELTA INC	CONE ANGLE
TIP	0.	25.400	25.400	63.54 58.04 53.62	2.26	0.057
1	5.	25.168	25.146	63.31 57.75 53.11	2.44	-0.478
2	10.	24.912	24.892	63.06 57.39 52.55	2.63	-0.425
3	15.	24.656	24.638	62.00 56.98 51.83	2.85	-0.370
4	30.	23.886	23.876	62.01 55.69 49.57	3.59	-0.198
5	50.	22.856	22.860	60.91 53.92 46.33	4.11	0.079
6	70.	21.829	21.844	59.75 52.02 42.55	4.33	0.277
7	85.	21.055	21.082	58.84 50.45 39.17	5.28	0.469
8	90.	20.797	20.828	58.53 49.86 37.83	5.44	0.552
9	95.	20.530	20.574	58.22 49.16 36.15	5.59	0.630
HUB	100.	20.320	20.320	57.95 48.52 34.34	5.72	0.057

RP	BLADE THICKNESSES			AXIAL DIMENSIONS			
	T1	TM	T0	ZIC	ZMC	ZTC	ZOC
TIP	0.051	0.151	0.051	0.336	1.557	1.695	2.965
1	0.051	0.158	0.051	0.325	1.558	1.679	2.962
2	0.051	0.167	0.051	0.313	1.559	1.662	3.011
3	0.051	0.176	0.051	0.299	1.559	1.643	3.022
4	0.051	0.201	0.051	0.255	1.559	1.584	3.090
5	0.051	0.233	0.051	0.194	1.560	1.497	3.186
6	0.051	0.264	0.051	0.126	1.560	1.400	3.290
7	0.051	0.286	0.051	0.069	1.560	1.319	3.377
8	0.051	0.293	0.051	0.048	1.559	1.289	3.411
9	0.051	0.300	0.051	0.023	1.558	1.255	3.450
HUB	0.051	0.306	0.051	-0.000	1.557	1.226	3.492

## Caractéristiques aérodynamiques

	unités	valeurs
<b>taux de compression</b>	[ - ]	1,257
<b>débit massique</b>	[ kg/s ]	9,46
<b>vitesse en tête</b>	[ m/s ]	243,8
<b>solidité en tête</b>	[ - ]	1,6
<b>allongement</b>	[ - ]	1
<b>nombre d'aubes</b>	[ - ]	50
<b>vitesse de rotation</b>	[ rad/s ]	960,28

## Propriétés matériau

Le matériau original du rotor 23B n'est pas défini dans le rapport de la NASA.

Propriétés considérées : un acier maraging de grade 200 :


	unité	valeurs
<b>alliage</b>	[ - ]	18-Ni-200-maraging
<b>module d'Young</b>	[ GPa ]	180
<b>masse volumique</b>	[ kg/m <sup>3</sup> ]	8000
<b>coefficient de Poisson</b>	[ - ]	0,3
<b>limite élastique</b>	[ GPa ]	1,38

Fréquences des trois premiers modes (noeuds de la base encastrés) pour le maillage :

1. (1B): 7194,7 rad/s / 1145,1 Hz

2. (1T): 15383,6 rad/s / 2448,4 Hz
3. (2B): 28053,6 rad/s / 4464,9 Hz

## CAO



1. <sup>a, b</sup> Britsch. «Design and overall performance of four highly loaded, high speed inlet stages for an advanced high-pressure-ratio core compressor » 1979. [pdf](#)

Document issu de la page wiki:

[https://lava-wiki.meca.polymtl.ca/public/modeles/rotor\\_23b/accueil?rev=1663351788](https://lava-wiki.meca.polymtl.ca/public/modeles/rotor_23b/accueil?rev=1663351788)

Dernière mise à jour: **2023/04/05 08:59**