

Rotor 57

- [Français](#)
- [English](#)

Downloadable files

×

Open access

[Git project](#)

About

Rotor 57 is part of a research program to study fan stages suitable for use in engines for quiet powered lift aircraft. Experimental studies have been conducted on fan stages suitable for use in engines for quiet powered lift aircraft using the externally blown flap. The externally blown flap aircraft requires a large flow of low velocity air for effective lift and low noise during take-off and landing. To meet the low noise requirement, the fans will be required to have low tip speed and low-pressure ratio. The pressure ratios of interest in the program range from 1.15 to 1.4. Rotor 57 has a pressure ratio of 1.38.

- Original technical report ^[1]:

```
@TechReport{moore1979design,
  author      = {Moore, Royce D. and Osborn, Walter M.},
  date       = {1979},
  institution = {NASA Lewis Research Center Cleveland, OH, United
States},
  title      = {Aerodynamic Performance of 1.38-Pressure-Ratio,
Variable-Pitch Fan Stage},
  number    = {NASA-TP-1502},
  url       = {https://ntrs.nasa.gov/citations/19790023042},
}
* Picture :

{{ :public:modeles:rotor_57:gene_aubes_nasa_image_rotor57.png?300 |}}
<caption>Fig1. https://ntrs.nasa.gov/citations/19790023042 p.56</caption>

<callout type="info" icon="true" title="Useful documents">
  * {{ :public:modeles:rotor_57:rotor57.pdf | NASA technical report}}
  (.pdf)
  * {{ :public:modeles:rotor_57:rotor57_original.csv | geometrical
parameters file}} (.csv), usable as input of
OpenMCAD[(cite:Kojtych_2022_gene_aubes>Kojtych S., Batailly A. «OpenMCAD,
an open blade generator: from Multiple-Circular-Arc profiles to Computer-
Aided Design model» 2022. {{ https://hal.science/hal-03923093|code en
```

libre accès}})] to generate reference blade models.

</callout>

==== Reference blade ====

The **reference blade** is defined with multiple-circular arc profiles[(cite:Crouse_1969_computer)] given in the original NASA report[(cite:moore1979design)]. Corresponding models are computed with the open-source code OpenMCAD[(cite:Kojtych_2022_gene_aubes)].

==== Geometry ====

The geometry of rotor 57 is described in the [[<https://ntrs.nasa.gov/citations/19790023042>|original NASA report]] by the following tables. The length are in centimeters and the angles in degrees.

{ { :public:modeles:rotor_57:gene_aubes_nasa_geom_rotor57.png?400 | } }

==== Aerodynamic design ====

^	^	unit	^	values	^
^	pressure ratio	[-]		1.38	
^	mass flow	[kg/s]		29.6	
^	tip speed	[m/s]		289.6	
^	aspect ratio	[-]		1.26	
^	number of blades	[-]		19	
^	rotative speed	[rad/s]		1139.98	

==== Material properties ====

The original material of the rotor 57 is not defined in the NASA report.

Considered properties: Ti-6Al-4V, generic titanium :

^	^	unité	^	valeurs	^
^	alloy	[-]		Ti-6Al-4V	
^	Young's modulus	[GPa]		108	
^	density	[kg/m3]		4400	
^	Poisson's ratio	[-]		0.34	
^	yield stress	[GPa]		0.824	

First three natural frequencies (with clamped root) for the mesh:

- <fc #c0c0c0>(1B)</fc>: 4256.6 rad/s / 677.5 Hz
- <fc #c0c0c0>(2B)</fc>: 11745.8 rad/s / 1869.4 Hz
- <fc #c0c0c0>(1T)</fc>: 14867.1 rad/s / 2366.2 Hz

==== CAD model ====

The CAD model is computed with the open source code OpenMCAD[(cite:Kojtych_2022_gene_aubes)].

```
<grid>
<col md="2">
</col>
<col md="4">
{{ :public:modeles:rotor_57:57_intra.png?200 |}}
  <caption>pressure side</caption>
</col>
<col md="4">
{{ :public:modeles:rotor_57:57_extra.png?200 |}}
<caption>suction side</caption>
</col>
<col md="2">
</col>
</grid>
```

==== Natural frequencies ====

First three natural frequencies (with clamped root) for the mesh computed with OpenMCAD[(cite:Kojtych_2022_gene_aubes)]:

```
<callout type="warning" icon="true">
Currently not available because of a problem to compute them with aster
from the mesh of the reference blade.
</callout>
```

```
</pane>
```

```
<pane id="tab-fr">
```

```
<btn type="warning" size="md" modal="modal_fr">Fichiers
téléchargeables</btn>
<modal id="modal_fr" title="Libre accès">
**[[https://gitlab.lava.polymtl.ca/depots_publics/modeles/nasa/rotor57|lie
n vers le projet Git]]**
</modal>
```

==== À propos =====

Le rotor 57 fait partie d'un programme de recherche visant à étudier les

étages de soufflante susceptibles d'être utilisés dans des moteurs d'avions plus silencieux. Des études expérimentales ont été menées sur des étages de soufflante utilisant un volet à soufflage externe. L'utilisation de tel volets nécessite un grand débit d'air à faible vitesse pour une portance efficace et un faible niveau de bruit au décollage et à l'atterrissage. Pour répondre à cette exigence de faible bruit, les soufflantes devront avoir une faible vitesse en tête et un faible taux de compression. Les taux de compression d'intérêt dans le programme varient de 1,15 à 1,4. Le rotor 57 possède un taux de compression de 1,38.

```
* Rapport technique original [(cite:moore1979design>)]:
<code>@TechReport{moore1979design,
  author      = {Moore, Royce D. and Osborn, Walter M.},
  date        = {1979},
  institution  = {NASA Lewis Research Center Cleveland, OH, United
States},
  title       = {Aerodynamic Performance of 1.38-Pressure-Ratio,
Variable-Pitch Fan Stage},
  number      = {NASA-TP-1502},
  url         = {https://ntrs.nasa.gov/citations/19790023042},
}
```

- Photographie :



C-77674

Fig1. <https://ntrs.nasa.gov/citations/19790023042> p.56

Documents utiles

- rapport technique original de la NASA (.pdf)
- [fichier de paramètres géométriques](#) (.csv), utilisable en entrée de OpenMCAD^[2] pour générer l'aube de référence

Aube de référence

L'**aube de référence** est définie par des profils de type arcs circulaires multiples^[3], donnés dans le rapport technique original de la NASA^[1]. Les modèles associés sont obtenus avec le code en libre accès OpenMCAD^[2].

Géométrie

La géométrie du rotor 57 est décrite dans le [rapport d'origine de la NASA](#) par les tableaux suivants. Les grandeurs sont en centimètres et en degrés.

TABLE IV. - BLADE GEOMETRY FOR ROTOR 57

RP	PERCENT RADII			BLADE ANGLES			DELTA INC	CONE ANGLE
	SPAN	RI	RO	KIC	KTC	KOC		
TIP	0.	25.400	25.400	54.70	48.96	43.29	2.32	-.057
1	5.	24.840	24.853	53.95	47.77	41.59	2.83	-.121
2	10.	24.253	24.305	53.16	46.52	39.88	3.29	-.494
3	15.	23.657	23.758	52.32	45.23	38.14	3.65	-.926
4	30.	21.826	22.116	49.35	40.34	31.33	4.33	2.412
5	50.	19.338	19.926	44.86	33.47	22.10	5.14	4.385
6	70.	16.831	17.737	40.11	24.97	9.84	7.18	6.189
7	85.	14.950	16.095	35.94	18.02	-.13	10.29	7.494
8	90.	14.349	15.577	32.74	14.72	-3.27	11.72	7.879
9	95.	13.763	15.000	28.62	10.89	-6.82	13.31	8.247
HUB	100.	13.208	14.453	24.19	6.93	-10.45	14.93	8.473

RP	BLADE THICKNESSES			AXIAL DIMENSIONS			
	TI	TM	TO	ZI	ZMC	ZTC	ZO
TIP	.015	.190	.017	1.646	4.248	4.248	7.162
1	.018	.211	.020	1.541	4.247	4.247	7.295
2	.021	.235	.023	1.431	4.250	4.250	7.437
3	.022	.264	.027	1.321	4.260	4.260	7.590
4	.030	.351	.037	.969	4.181	4.181	7.852
5	.040	.482	.050	.543	4.129	4.129	8.218
6	.054	.655	.064	.182	4.102	4.102	8.536
7	.069	.842	.085	.067	4.195	4.195	8.772
8	.082	.981	.098	.042	4.185	4.185	8.705
9	.100	1.159	.114	.020	4.149	4.149	8.553
HUB	.119	1.350	.132	-.000	4.103	4.103	8.355

Caractéristiques aérodynamiques

	unités	valeurs
taux de compression	[-]	1,38
débit massique	[kg/s]	29,6
vitesse en tête	[m/s]	289,6
allongement	[-]	1,26
nombre d'aubes	[-]	19
vitesse de rotation	[rad/s]	1139,98

Propriétés matériau

Le matériau original du rotor 57 n'est pas défini dans le rapport de la NASA.

Propriétés considérées : alliage de titane Ti-6Al-4v :

	unité	valeurs
alliage	[-]	Ti-6Al-4v

	unité	valeurs
module d'Young	[GPa]	108
masse volumique	[kg/m3]	4400
coefficient de Poisson	[-]	0,34
limite élastique	[GPa]	0,824

Fréquences des trois premiers modes (noeuds de la base encastrés) pour le maillage :

1. (1B): 4256,6 rad/s / 677,5 Hz
2. (2B): 11745,8 rad/s / 1869,4 Hz
3. (1T): 14867,1 rad/s / 2366,2 Hz

Modèle CAO



intrados

</col>



extrados

Fréquences propres

Fréquences des trois premiers modes (noeuds du pied d'aube encastrés) pour le maillage obtenu avec OpenMCAD^[2] :

Il y a actuellement un problème sur le calcul des fréquences propres dans Aster.

</tabs>

1. ^{a, b} Moore R. D., Osborn W. M. «Aerodynamic Performance of 1.38-Pressure-Ratio, Variable-Pitch Fan Stage» 1979. [pdf](#)
2. ^{a, b, c} Kojtych S., Batailly A. «OpenMCAD, an open blade generator: from Multiple-Circular-Arc profiles to Computer-Aided Design model» 2022. [code en libre accès](#)
3. ^a Crouse *et al.* «A computer program for composing compressor blading from simulated circular-arc elements on conical surfaces » 1969. NASA-TN-D-5437. [pdf](#)

Document issu de la page wiki:

https://lava-wiki.meca.polymtl.ca/public/modeles/rotor_57/accueil?rev=1681096383

Dernière mise à jour: **2023/04/09 23:13**